

COPIER

Copying process:	Laser beam scanning and electro-photographic printing
Copy speed:	20/20 copies per minute
Resolution:	600 dpi
Multiple copy:	Up to 99
Warm-up time:	Less than 30/30 seconds
First output speed:	Less than 7.5 seconds
Zoom:	50 - 200% (in 1% steps)
Memory:	Standard: 256/640 MB Maximum: MP 201SPF: 640 MB + 80 GB Hard Disk Drive
Paper input capacity:	Standard: 1 x 250-sheet paper tray(s) 100-sheet multi bypass tray ¹ Maximum: 1,350 sheets
Paper output capacity:	250 sheets
Paper size:	Standard paper tray: A5 - A4 Optional paper tray(s) Bypass tray: A62 - A4 Duplex tray: A5 - A4
Paper weight:	Paper trays: 60 - 90 g/m ² Optional paper tray(s): 60 - 90 g/m ² Bypass tray: 60 - 157 g/m ² Duplex tray: 64 - 90 g/m ²
Duplexing:	Standard
Dimensions (W x D x H):	485 x 450 x 481 mm
Weight:	Less than 29 kg (with ARDF)
Power source:	220 - 240 V, 50 - 60 Hz
Power consumption:	Maximum: Less than 930 W

PRINTER (MP 201SPF)

CPU:	RM5231 400MHz
Print speed:	20 prints per minute
Printer language:	Standard: PCL5e, PCL6, PostScript® 3™
Interface:	Standard: Ethernet 10 base-T/100 base-TX, USB2.0 Option: IEEE 1284, Wireless LAN (IEEE 802.11a/b/g, WPA support), Gigabit Ethernet
Memory:	640 MB + optional 80 GB Hard Disk Drive
Network protocol:	TCP/IP (IPv4, IPv6), IPX/SPX, Appletalk, SMB
Supported environments:	Windows®2000/XP/Server 2003/Vista/Server 2008, Macintosh 8.6 - 9.x (OS X Classic), Macintosh X v10.1 or later (native mode), Sun® Solaris 2.6/7/8/9/10, HP-UX 10.x/11.x/11iv2/11iv3, RedHat® Linux 6.x/7.x/8.x/9.x/Enterprise, SCO OpenServer 5.0.6/5.0.7/6.0, IBM® AIX v4.3/5L v5.1/5L v5.2/5L v5.3, Novell® Netware® 3.12/3.2/4.1/4.11/5.0/5.1/6.0/6.5

SCANNER (MP 201SPF)

Scan speed:	Full colour: Maximum 10 originals per minute B/W: Maximum 22 originals per minute
Resolution:	Maximum 600 dpi (TWAIN: 100 - 600 dpi)
Original size:	A5 - A4
Output formats:	TIFF, PDF, JPEG
Bundled drivers:	Network TWAIN
Scan to e-mail:	SMTP, TCP/IP (IPv4)
Destination addresses:	Maximum 100 per job
Stored destination addresses:	Maximum 150
Address book:	Via LDAP or locally
Scan to folder:	SMB, FTP or NCP protocol
Destination:	Maximum 32 folders per job

SOFTWARE SOLUTIONS (MP 201SPF)

Web Image Monitor
SmartDeviceMonitor™
DeskTopBinder™ Lite
Web SmartDeviceMonitor™

FAX (MP 201F/MP 201SPF)

Circuit:	PTSN, PBX
Compatibility:	ITU-T (CCITT) G3
Modem speed:	Maximum 33.6 Kbps
Resolution:	200 x 100 - 200 dpi; 8 x 15.4 l/mm (send only)
Compression method:	MH, MR, MMR, JBIG
Scanning speed:	2 seconds
Memory capacity:	Standard: 4 MB
Memory backup:	Yes (12 hours)

OTHER OPTIONS

MP 201F/MP 201SPF:	1 x 500-sheet paper tray (maximum 2 optional paper trays can be installed), Accessibility handle (for standard tray only), Counter interface unit
MP 201SPF only:	80 GB HDD, Wireless LAN, IEEE 1284, Data Overwrite Security Unit, HDD encryption unit, VM card, Scan to SD/USB, Gigabit Ethernet, Professional software solutions, Remote Communication Gate BN1

¹ Bypass tray and duplex unit do not work together.

² Manual input.

Ricoh has designed these products to meet EC ENERGY STAR guidelines for energy efficiency.

For availability of models, options and software, please consult your local Ricoh supplier.