

Aficio™ MP 2510/MP 3010

Specifications



COPIER

Copying process:	Twin laser beam scanning & electro photographic printing	
Copy speed:	25/30 copies per minute	
Resolution:	600 dpi	
Multiple copy:	Up to 999	
Warm up time:	12 seconds	
First output speed:	4.4 seconds	
Zoom:	25 - 400% (in 1% steps)	
Memory:	Standard:	128 MB
	Maximum:	384 MB + 40 GB Hard Disk Drive
Paper input capacity:	Standard:	2 x 500-sheet paper trays
	Maximum:	3,100 sheets
Paper output capacity:	Standard:	500 sheets
	Maximum:	1,625 sheets
Paper size:	A6 - A3	
Paper weight:	Paper tray 1:	60 - 105 g/m ²
	Paper tray 2/bypass tray:	52 - 157 g/m ²
	Duplex tray:	64 - 105 g/m ²
Dimensions		
(W x D x H):	550 x 604 x 980 mm	
Weight:	Less than 62 kg	
Power source:	220 - 240 V, 50/60 Hz	
Power consumption:	Operation:	Maximum 1.32 kW
	Energy saver mode:	Less than 120 W

PRINTER/SCANNER (option)



Printer

Print speed:	25/30 prints per minute		
Printer language:	Standard:	PCL5e, PCL6, RPCS™	
	Option:	Adobe® PostScript® 3™	
Resolution:	Maximum 600 x 600 dpi		
Interface:	Standard:	USB 2.0	
		Ethernet 10 base-T/100 base-TX	
	Option:	Bi-directional IEEE 1284	
		Wireless LAN (IEEE 802.11b)	
		Bluetooth	
Memory:	384 MB + 40 GB Hard Disk Drive		
Network protocol:	TCP/IP, IPX/SPX, SMB, AppleTalk		
Supported environments:	Windows® 95/98/Me/NT4.0/2000/XP/		
	Server 2003		
	Novell® NetWare® 3.12/3.2/4.1/4.11/5.0		
	5.1/6/6.5		
	UNIX Sun® Solaris 2.6/7/8/9/10		
	HP-UX 10.x/11.x/11iv2		
	SCO OpenServer 5.0.6/5.0.7		
	RedHat® Linux 6.x/7.x/8.x/9.x/Enterprise		
	IBM® AIX v4.3/5L v5.1/5L v5.2/5.3		
	Macintosh 8.6 or later (OS X Classic)		
	Macintosh X v10.1 or later (native mode)		
	SAP® R/3® (3.x or later)		
	NDPS Gateway Network 5.1 (SP8 or later)		
	6.0 (SP5 or later)/6.5 (SP3 or later)		
IBM® iSeries / AS/400 using			
OS/400 Host Print Transform			



Scanner

Scan speed:	Maximum 52 originals per minute (MH, A4/LEF)
Resolution:	Maximum 600 dpi (TWIN: 1,200 dpi)
Original size:	A5 - A3
Bundled drivers:	Network TWIN
Scan to e-mail:	SMTP, TCP/IP
Destination addresses:	Maximum 500 per job
	(stored: maximum 2,000)
Address book:	Via LDAP or locally on Hard Disk Drive
Scan to folder:	SMB, FTP, NCP protocol (with login security)
Destination:	Maximum 50 folders per job



Software

SmartDeviceMonitor™, Web SmartDeviceMonitor™ 2
Web Image Monitor, DeskTopBinder™ Lite



RPCS™ PRINTER UNIT (option)

Print speed:	25/30 prints per minute	
Printer language:	Standard:	RPCS™
	Option:	PCL5e, PCL6, Adobe® PostScript® 3™
Resolution:	Maximum 600 x 600 dpi	



FAX (option)

Circuit:	PSTN, PBX	
Compatibility:	ITU-T (CCITT) G3	
	ITU-T (T.37) Internet Fax	
	ITU-T (T.38) IP Fax	
Modem speed:	Maximum 33.6 Kbps	
Resolution:	Standard/detail:	200 x 100/200 dpi
	Maximum:	400 x 400 dpi (option)
Compression method:	MH, MR, MMR, JBIG	
Scanning speed:	Less than 0.56 seconds (200 x 100 dpi, A4/SEF)	
Memory:	Standard/maximum:	12/44 MB
Memory backup:	Yes	

OTHER OPTIONS

Platen cover, 50-sheet Automatic Reverse Document Feeder, 100-sheet multi-bypass tray, 2 x 500-sheet paper trays, 2,000-sheet large capacity tray, 125-sheet one-bin tray, 500-sheet finisher, 1,000-sheet finisher, Shift sort tray, Duplex unit, 40 GB Hard Disk Drive, 2nd Super G3 port, Data Overwrite Security Unit, Copy Data Security Unit, File Format Converter, User Account Enhance Unit, Browser Unit, Scanner upgrade (for printer option), Printer upgrade (for RPCS™ printer unit), VM Card (Java™), Key Counter Bracket, PI Board, Bridge Unit, Interchange Unit, Professional software solutions

For availability of models, optional apparatus and software, please consult your local Ricoh supplier.