

COPIER

Copying process:	Laser beam scanning & electro photographic printing		
Copy speed:	MP C2000:		
	B/W / full colour:	20 copies per minute ¹	
	MP C2500:		
	B/W / full colour:	25 copies per minute ¹	
	MP C3000:		
	B/W / full colour:	30 copies per minute ¹	
Resolution:	600 dpi		
Multiple copy:	Up to 999		
Warm up time:	Less than 45 seconds		
First output speed:	Black and white:	6.7 seconds	
	Full colour:	9.7 seconds	
Zoom:	25 - 400% (in 1% steps)		
Memory:	Standard:	1,024 MB + 40 GB Hard Disk Drive	
Paper input capacity:	Standard:	2 x 550-sheet paper trays 1 x 100-sheet bypass tray	
	Maximum:	3,200 sheets	
Paper output capacity:	Maximum:	1,500 sheets	
Paper size:	A6 - A3		
Paper weight:	Paper trays:	60 - 216 g/m ²	
	Bypass tray:	60 - 256 g/m ²	
	Duplex tray:	64 - 169 g/m ²	
Dimensions (W x D x H):	650 x 659 x 740 mm		
Weight:	Less than 120 kg (with ARDF)		
Power source:	220 - 240 V, 50/60 Hz		
Power consumption:	Operation:	Maximum 1.5 kW	
	Energy saver mode:	Less than 99 W	
	Auto Off mode:	Less than 8 W	

PRINTER

Print speed:	MP C2000:		
	B/W / full colour:	20 prints per minute	
	MP C2500:		
	B/W / full colour:	25 prints per minute	
	MP C3000:		
	B/W / full colour:	30 prints per minute	
Printer language:	Standard:	PCL5c, PCL6, RPCS™	
	Option:	Adobe® PostScript® 3™	
Resolution:	600 x 600 dpi/2,400 x 600 dpi (equivalent)		
Interface:	Standard:	USB 2.0	
		Ethernet 10 base-T/100 base-TX	
	Option:	Bi-directional IEEE 1284	
		FireWire (IEEE 1394)	
		Wireless LAN (IEEE 802.11b)	
		Bluetooth	
		USB Host I/F	
Network protocol:	TCP/IP, IPX/SPX, AppleTalk		
Supported environments:	Windows® 95/98/Me/NT4.0/2000/XP/Server 2003/Vista		
	Novell® NetWare® 3.12/3.2/4.1/4.11/5.0/5.1/6/6.5		
	UNIX: Sun® Solaris 2.6/7/8/9/10		
	HP-UX 10.x/11.x/11iv1/11iv2		
	SCO OpenServer 5.0.6/5.0.7/6.0		
	RedHat® Linux 6.x/7.x/8.x/9.x/Enterprise		
	IBM® AIX v4.3/5L v5.1/5L v5.2/5L v5.3		
	Macintosh 8.6 or later (OS X Classic)		
	Macintosh X v10.1 or later (native mode)		
	IBM® System i5™ HPT		
	SAP® R/3®		
	NDPS Gateway		
	AS/400® using OS/400 Host Print Transform		

SCANNER

Scan speed:	Maximum 50 originals per minute (MH, A4)
Resolution:	Maximum 1,200 dpi (1,200 dpi TWAIN black and white, greyscale)
Original size:	A5 - A3
Output formats:	PDF/JPEG/TIFF/High compression PDF
Bundled drivers:	Network, TWAIN
Scan to e-mail:	SMTP (optionally with POP authentication)
Destination addresses:	Maximum 500 per job
Stored destination addresses:	Maximum 2,000
Address book:	Via LDAP or locally on Hard Disk Drive
Scan to folder:	SMB or FTP protocol (with login security)
Destination:	Maximum 50 folders per job

SOFTWARE

- SmartDeviceMonitor™
- Web SmartDeviceMonitor™
- Web Image Monitor
- DeskTopBinder™ Lite

FAX (OPTION)

Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3, ITU-T (T.37) Internet fax, ITU-T (T.38) IP fax
Modem speed:	Maximum 33.6 Kbps
Resolution:	Standard/detail: 200 x 100/200 dpi Maximum: 400 x 400 dpi (option)
Compression method:	MH, MR, MMR, JBIG
Scanning speed:	0.40 seconds (A4, LEF, standard/detail mode)
Memory capacity:	Standard: 4 MB Maximum: 28 MB
Memory backup:	Yes

OTHER OPTIONS

- Platen cover
- 50-sheet Auto Reverse Document Feeder
- 2 x 550-sheet paper trays
- 2,000-sheet large capacity tray
- 500-sheet finisher
- 1,000-sheet multi-tray finisher
- 1,000-sheet booklet finisher
- Several punch kits
- Shift sort tray
- One bin tray
- Bridge unit
- Adobe® PostScript® 3™
- Bi-directional IEEE 1284
- FireWire (IEEE 1394)
- Wireless LAN (IEEE 802.11b)
- Bluetooth
- USB Host I/F
- Camera Direct Print card
- 2nd G3 port
- SAF memory
- Data Overwrite Security Unit
- Copy Data Security Unit
- Professional software solutions

1 Simplex.

For availability of models, optional apparatus and software, please consult your local Ricoh supplier.