

MP 2001SP/MP 2501SP

MAIN SPECIFICATIONS

GENERAL

Warm-up time:	20/20 seconds
First output speed:	6/6 seconds
Continuous output speed:	20/25 pages per minute
Memory:	Standard: 1 GB Maximum: 1.5 GB
HDD:	Option: 250 GB
Dimensions (W x D x H):	587 x 568 x 460 / 587 x 568 x 558 mm
Weight:	38/44 kg
Power source:	220-240 V, 50/60 Hz

COPIER

Copying process:	Laser beam scanning and electro-photographic printing
Multiple copying:	Up to 999 copies
Resolution:	600 dpi
Zoom:	From 50% to 200%

PRINTER

Printer language:	Standard: PCL5e, PCL6, PDF Option: Adobe® PostScript® 3™,
Print resolution:	600 x 600 dpi
Interface:	Standard: USB 2.0, SD slot, USB Host I/F, Ethernet 10 base-T/100 base-TX, Ethernet 1000 Base-T Option: Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/b/g), Bluetooth
Network protocol:	TCP/IP (IP v4, IP v6), IPX/SPX
Windows® environments:	Windows® XP, Windows® Vista, Windows® 7, Windows® Server 2003, Windows® Server 2008, Windows® Server 2008R2
Mac OS environments:	Macintosh OS X v10.5 or later
UNIX environments:	UNIX Sun® Solaris: 2.6, 2.7, 2.8, 2.9, 2. 10 HP-UX: 10.x, 11.x, 11i v2, 11i v3, SCO OpenServer: 5.0.6, 5.0.7, 6.0 RedHat® Linux Enterprise: 4, 5, 6 IBM® AIX: 5L v5.3, 5L v6.1, 5Lv7.1 IBM® System i5™ HPT
Novell® Netware® environments:	v6.5
SAP® R/3® environments:	SAP® R/3.x or later mySAP ERP 2004 or later
Citrix environments:	Citrix Presentation Server 4.0, 4.5 Xen App 5.6, 6.0, 6.5

SCANNER

Scanning speed:	Full colour: Maximum 50 originals per minute B/W: Maximum 50 originals per minute
Resolution:	Maximum: 600 dpi, 1200 dpi (TWAIN)
Original size:	A3, A4, A5
File format:	TIFF, JPEG, PDF, Encrypt PDF, High compression PDF, PDF-A
Bundled drivers:	Network TWAIN, Scanner utility
Scan to:	E-mail, Folder, USB/SD, URL, WSD Scanner

FAX (OPTION)

Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3
Resolution:	8 x 3.85 line/mm, 200 x 100dpi 8 x 7.7 line/mm, 200 x 200dpi
Transmission speed:	G3: Approx 2 seconds (200 x 100dpi, JBIG) Approx 3 seconds (200 x 100dpi)
Modem speed:	Maximum: 33.6 Kbps
Scanning speed:	2 second(s)
Memory capacity:	Standard: 4 MB

PAPER HANDLING

Recommended paper size:	Paper tray(s): A5 - A3 Bypass tray: A6 - A3
Paper input capacity:	Standard: 350/600 sheets Maximum: 1,350/1,600 sheets
Paper output capacity:	Standard: 250 sheets Maximum: 350 sheets
Paper weight:	Standard paper tray(s): 60-105 g/m² Bypass tray : 60-162 g/m² Duplex : 64-90 g/m²

ECOLOGY

Power consumption:	Maximum: 1.55 kW Ready mode: 113W Sleep mode: 0.6 W TEC (Typical Electricity Consumption): 892/1,082 W/h
--------------------	--

SOFTWARE

Standard:	Smart Device Monitor, Web Smart Device Monitor® Web Image Monitor
Optional:	Global Scan NX Card Authentication Package

OPTIONS

ADF handle, Platen cover, ARDF, 1 x 500-sheet paper tray, 2 x 500-sheet paper tray, One-bin tray, Hard disk drive, RAM, VM card, Netware, Browser unit, Adobe® PostScript® 3™ option, Counter interface, File format converter, Copy data security unit, Wireless LAN (IEEE 802.11a/g), IEEE 1284, Bluetooth, Fax option, Fax connection unit, Fax marker

For availability of models, options and software, please consult your local Ricoh supplier.