

MP C3002/MP C3502

MAIN SPECIFICATIONS

Aficio®

GENERAL

Warm-up time:	20 seconds
First output speed:	Full colour: 7.3/7.2 seconds B/W: 4.8 seconds
Continuous output speed:	MP C3002: B/W / Full colour: 30 ppm MP C3502: B/W / Full colour: 35 ppm
Memory:	1.5GB RAM / 190 GB HDD (Standard)
Dimensions (W x D x H):	With ARDF: 670 x 682 x 880 mm
Weight:	120 kg
Power source:	220 - 240 V, 50/60 Hz

COPIER

Copying process:	Dry electrostatic transfer system
Multiple copying:	Up to 999 copies
Copy resolution:	600 dpi
Zoom:	From 25% to 400% in 1% steps

PRINTER

Printer language:	Standard: PCL5c, PCL6 Option: Adobe® PostScript® 3™, IPDS
Print resolution:	Maximum: 1,200 dpi x 1,200 dpi
Interface:	Standard: USB 2.0, SD slot, Ethernet 10 base-T/100 base-TX Option: Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/g), Bluetooth, Ethernet 1000 Base-T
Network protocol:	Standard: TCP/IP (IP v4, IP v6) Option: IPX/SPX
Windows® environments:	Windows® XP, Windows® Vista, Windows® 7, Windows® Server 2003, Windows® Server 2008, Windows® Server 2008R2
Mac OS environments:	Macintosh OS X Native v10.2 or later
UNIX environments:	UNIX Sun® Solaris: 2.6, 2.7, 2.8, 2.9, 2.10 HP-UX: 10.x, 11.x, 11i v2, 11i v3 SCO OpenServer: 5.0.6, 5.0.7, 6.0 RedHat® Linux: 4, 5, 6 IBM® AIX: 5L v5.3, 5L v6.1, 5Lv7.1
Novell® Netware® environments:	v6.5
SAP® R/3® environments:	SAP® R/3®

SCANNER

Scanning speed:	B/W / Full Colour: Maximum 51 ipm (LEF, A4, 200 dpi)
Scanning resolution:	B/W and Full Colour: 100-600 dpi Maximum: 1,200 dpi for TWAIN Scanning
Bundled drivers:	Network TWAIN
Scan to e-mail:	SMTP, POP, IMAP4
Scan to folder:	SMB, FTP, NCP

FAX (OPTION)

Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3
Resolution:	Standard: 8 x 3.85 line/mm, 200 x 100 dpi 8 x 7.7 line/mm, 200 x 200 dpi Option: 8 x 15.4 line/mm, 400 x 400 dpi, 16 x 15.4 line/mm, 400 x 400 dpi
Transmission speed:	2 second(s)
Modem speed:	Maximum: 33.6 Kbps
Scanning speed:	1 second(s)
Memory capacity:	Standard: 4 MB Maximum: 28 MB

PAPER HANDLING

Recommended paper size:	A3, A4, A5, B4, B5, A6
Paper input capacity:	Maximum: 4,400 sheets
Paper output capacity:	Maximum: 1,625 sheets
Paper weight:	Paper trays: 52 - 256 g/m² Bypass tray: 52 - 300 g/m² Duplex unit: 52 - 169 g/m²

ECOLOGY

Power consumption:	Maximum: 1,700 W Operating power: 700 W Ready mode: 90 W Low power mode: 67 W Sleep mode: 1.6 W TEC (Typical Electricity Consumption): MP C3002: 1.36 kW/h MP C3502: 1.55 kW/h
--------------------	---

SOFTWARE

Standard:	SmartDeviceMonitor, Web SmartDeviceMonitor®, Web Image Monitor
Optional:	GlobalScan NX, Card Authentication Package, Unicode Font Package for SAP, Remote Communication Gate S Pro

OPTIONS

ADF handle, 1 x 550-sheet paper tray, 2 x 550-sheet paper tray, 1,200-sheet side large capacity tray, 2,000-sheet large capacity tray, Bridge unit, 500-sheet finisher, 1,000-sheet finisher, 1,000-sheet booklet finisher, Punch kits, Internal shift tray, One-bin tray, Side tray, Envelope feeder, Caster table, Pictbridge, Browser unit, Counter interface, File format converter, Key counter bracket, Card reader bracket, Copy Data Security Unit, Fax Connection Unit, 2nd Super G3 port, Netware

For availability of models, options and software, please consult your local Ricoh supplier.