

MP C4502/MP C4502A/MP C5502/MP C5502A

Aficio®

MAIN SPECIFICATIONS

GENERAL

Warm-up time:	MP C4502/A: 19 seconds MP C5502/A: 21 seconds
First output speed:	MP C4502/A: B/W / Full colour: 3.6/5.7 seconds MP C5502/A: B/W / Full colour: 3.1/4.8 seconds
Continuous output speed:	MP C4502/A: B/W / Full colour: 45 ppm MP C5502/A: B/W / Full colour: 55 ppm 2GB RAM / 190 GB HDD (standard)
Memory:	2GB RAM / 190 GB HDD (standard)
Dimensions (W x D x H):	670 x 682 x 895 mm with ARDF 670 x 682 x 930 mm with SPDF
Weight:	MP C4502/C5502: 130 kg MP C4502A/C5502A: 133 kg
Power source:	220 - 240 V, 50/60 Hz

COPIER

Copying process:	Dry electrostatic transfer system
Multiple copying:	Up to 999 copies
Copy resolution:	600 dpi
Zoom:	From 25% to 400% in 1% steps

PRINTER

Printer language:	Standard: PCL5c, PCL6 Option: Adobe® PostScript® 3™, IPDS
Print resolution:	Maximum 1,200 x 1,200 dpi
Interface:	Standard: USB 2.0, SD slot, Ethernet 10 base-T/100 base-TX Option: Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/g), Bluetooth, Ethernet 1000 Base-T
Network protocol:	Standard: TCP/IP (IP v4, IP v6) Option: IPX/SPX
Windows® environments:	Windows® XP, Windows® Vista, Windows® 7, Windows® Server 2003, Windows® Server 2008, Windows® Server 2008R2
Mac OS environments:	Macintosh OS X v10.2 or later
UNIX environments:	UNIX Sun® Solaris: 2.6, 2.7, 2.8, 2.9, 2.10 HP-UX: 10.x, 11.x, 11i v2, 11i v3 SCO OpenServer: 5.0.6, 5.0.7, 6.0 RedHat® Linux Enterprise: 4, 5, 6 IBM® AIX: 5L v5.3, v6.1, v7.1
Novell® Netware® environments:	v6.5
SAP® R/3® environments:	SAP® R/3®

SCANNER

Scanning speed:	MP C4502/C5502: B/W / Full colour: 67 ipm MP C4502A/C5502A: B/W / Full colour: 85 ipm Simplex, 116 ipm Duplex
Scanning resolution:	B/W and Full colour: 100-600 dpi Maximum: 1,200dpi for TWAIN scanning
Bundled drivers:	Network TWAIN
Scan to e-mail:	SMTP, POP, IMAP4
Scan to folder:	SMB, FTP, NCP

FAX (OPTION)

Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3
Resolution:	Standard: 8 x 3.85 line/mm, 200 x 100 dpi 8 x 7.7 line/mm, 200 x 200 dpi Option: 8 x 15.4 line/mm, 400 x 400dpi 16 x 15.4 line/mm, 400 x 400 dpi
Transmission speed:	2 second(s)
Modem speed:	Maximum: 33.6 Kbps
Scanning speed:	0.7 second(s)
Memory capacity:	Standard: 4 MB Maximum: 28 MB

PAPER HANDLING

Recommended paper size:	A3, A4, A5, A6, B4, B5
Paper input capacity:	Maximum: 4,400 sheets
Paper output capacity:	Maximum: 3,625 sheets
Paper weight:	Paper trays: 52 - 256 g/m² Bypass tray: 52 - 300 g/m² Duplex tray: 52 - 169 g/m²

ECOLOGY

Power consumption:	Maximum: 1,700 W Operating power: 900 W Ready mode: MP C4502/C5502: 116 W MP C4502A/C5502A: 127 W Low power mode: MP C4502/C5502: 91 W MP C4502A/C5502A: 100 W Sleep mode: 1.5W TEC (Typical Electricity Consumption): MP C4502/A: 2.19 kW/h MP C5502/A: 2.79 kW/h
--------------------	---

SOFTWARE

Standard:	SmartDeviceMonitor, Web SmartDeviceMonitor®, Web Image Monitor
Optional:	GlobalScan NX, Card Authentication Package, Unicode Font Package for SAP, Remote Communication Gate S Pro

OPTIONS

ADF handle, 2 x 550-sheet paper tray, 1,200-sheet side large capacity tray, 2,000-sheet large capacity tray, Bridge unit, 1,000-sheet finisher, 3,000-sheet finisher, 2,000-sheet booklet finisher, Punch kits, Internal shift tray, One-bin tray, Side tray, Envelope feeder, Netware, Pictbridge, Browser unit, Counter interface, File format converter, Key counter bracket, Card reader bracket, Copy Data Security Unit, Fax Connection Unit, 2nd Super G3 port, Scanner accessibility option, Netware, Low cabinet

For availability of models, options and software, please consult your local Ricoh supplier.