

Aficio™ 3035/3045

Specifications



COPIER

Copying process:	Twin laser beam scanning & electro photographic printing		
CPU:	RM7035C-466 466 MHz		
Copy speed:	35/45 copies per minute		
Resolution:	600 dpi		
Multiple copy:	Up to 999		
Warm up time:	15/20 seconds		
First output speed:	4.3/3.6 seconds		
Zoom:	25 - 400% (in 1% steps)		
Memory:	Standard:	128 MB + 40 GB Hard Disk Drive	
	Maximum:	384 MB + 40 GB Hard Disk Drive	
Paper input capacity:	Standard:	2 x 500-sheet paper trays 1 x 50-sheet bypass tray	
	Maximum:	3,550 sheets	
Paper output capacity:	Standard:	500 sheets	
	Maximum:	2,875 sheets	
Paper size:	A6 - A3		
Paper weight:	Paper tray 1 & 2/duplex tray:	64 - 105 g/m ²	
	Paper tray 3 & 4:	60 - 105 g/m ²	
	Bypass tray:	52 - 163 g/m ²	
Dimensions			
(W x D x H):	670 x 650 x 720 mm		
Weight:	Less than 79 kg		
Power source:	220 - 240 V, 50/60 Hz		
Power consumption:	Operation:	Maximum 1.5 kW	
	Energy saver mode:	Aficio 3035 130 W	
		Aficio 3045 149 W	
	Auto Off mode:	8.5 W	

PRINTER/SCANNER (option)



Printer

Print speed:	35/45 prints per minute		
Printer language:	Standard:	PCL5e, PCL6, RPCS™	
	Option:	Adobe® PostScript® 3™	
Resolution:	Maximum 600 x 600 dpi (2,400 dpi equivalent x 600 dpi with smoothing)		
Interface:	Standard:	USB 2.0	
	Option:	Ethernet 10 base-T/100 base-TX Bi-directional IEEE 1284 FireWire (IEEE 1394) Wireless LAN (IEEE 802.11b) Bluetooth	
Memory:	384 MB + 40 GB Hard Disk Drive		
Network protocol:	TCP/IP, IPX/SPX, SMB, AppleTalk		
Supported environments:	Windows® 95/98/Me/NT4.0/2000/XP/		
	Server 2003		
	Novell® NetWare® 3.12/3.2/4.1		
	4.11/5.0/5.1/6/6.5		
	UNIX Sun® Solaris 2.6/7/8/9/10		
	HP-UX 10.x/11.x/11i/11i		
	SCO OpenServer 5.0.6/5.0.7		
	RedHat® Linux 6.x/7.x/8.x/9.x/Enterprise		
	IBM® AIX v4.3/5L v5.1/5L v5.2/5.3		
	Macintosh 8.6 or later (OS X Classic)		
	Macintosh X v10.1 or later (native mode)		



Scanner

Scan speed:	Maximum 52 originals per minute (MH, A4/LEF)
Resolution:	Maximum 600 dpi (TWAIN: 1,200 dpi)
Original size:	A5 - A3
Output formats:	PDF/JPEG/TIFF
Bundled drivers:	Network TWAIN
Scan to e-mail:	SMTP, TCP/IP
Destination addresses:	Maximum 500 per job
Stored destination addresses:	Maximum 2,000
Address book:	Via LDAP or locally on Hard Disk Drive
Scan to folder:	SMB, FTP, NCP protocol (with login security)
Destination:	Maximum 50 folders per job



Software*

SmartDeviceMonitor™, Web SmartDeviceMonitor™
Web Image Monitor, DeskTopBinder™ Lite
* Bundled with printer/scanner option.



FAX (option)

Circuit:	PSTN, PBX		
Compatibility:	ITU-T (CCITT) G3, additional G3 option		
	ITU-T (T.37) Internet Fax		
	ITU-T (T.38) Internet Fax		
Modem speed:	Maximum 33.6 Kbps		
Resolution:	Standard/detail:	200 x 100/200 dpi	
	Superfine:	400 x 400 dpi (option)	
Compression method:	MH, MR, MMR, JBIG		
Scanning speed:	Less than 0.43 seconds		
	(200 x 100/200 dpi, A4/SEF)		
SAF memory:	Standard:	4 MB	
	Maximum:	28 MB	
Memory backup:	Yes		

OTHER OPTIONS

Platen cover, 80-sheet Automatic Reverse Document Feeder,
2 x 500-sheet paper trays, 1,500-sheet large capacity tray,
125-sheet one-bin tray, 1,000-sheet finisher (3 position stapling),
2,500-sheet multi-tray finisher (4 position stapling), 1,150-sheet
booklet finisher (4 position stapling), 2/4 hole punch unit,
2nd Super G3 port, Adobe® PostScript® 3™, Wireless LAN (IEEE 802.11b),
Bluetooth, FireWire (IEEE 1394), Bi-directional IEEE 1284,
Data Overwrite Security Unit, Copy Data Security Unit,
File Format Converter, User Account Enhance Unit, Browser Unit,
VM Card, Key Counter Bracket, PI Board, Scanner accessibility option,
Fax Marker, Professional software solutions

For availability of models, optional apparatus and software, please consult
your local Ricoh supplier.