

### COPIER

Copying process:	Dry electrostatic transfer system
Copy speed:	MP C2030: B/W / full colour: 20 copies per minute MP C2530: B/W / full colour: 25 copies per minute
Resolution:	600 dpi
Multiple copy:	Up to 999
Warm-up time:	Less than 25 seconds <sup>1</sup>
First output speed:	Black and white: 6.5 seconds Full colour: 9.5 seconds
Zoom:	25 - 400% (in 1% steps)
Memory:	Standard: 512 MB
Paper input capacity:	Standard: 2 x 250-sheet paper trays 1 x 100-sheet bypass tray Maximum: 1,600 sheets
Paper output capacity:	Maximum: 650 sheets
Paper size:	A6 - A3
Paper weight:	Paper trays 1: 60 - 256 g/m <sup>2</sup> Paper trays 2: 60 - 169 g/m <sup>2</sup> Bypass tray: 60 - 256 g/m <sup>2</sup> Duplex tray: 60 - 105 g/m <sup>2</sup>
Dimensions (W x D x H):	587 x 655 x 845 mm (with ARDF)
Weight:	Less than 100 kg (with ARDF)
Power source:	220 - 240 V, 50/60 Hz
Power consumption:	Operation: Maximum 1,680 W <sup>1</sup>

### PRINTER

Print speed:	MP C2030: B/W / full colour: 20 prints per minute MP C2530: B/W / full colour: 25 prints per minute
Printer language:	Standard: RPCS™ Option: PCL5c, PCL6
Resolution:	600 dpi
Interface:	USB 2.0 Host USB Device Ethernet 10 base-T/100 base-TX
Supported environments:	Windows® 2000/XP/Vista/Server 2003/Server 2008 IBM iSeries AS/400 <sup>1</sup> using OS/400 Host Print Transform


### SCANNER

Scan speed:	B/W: 41 images per minute (LEF, A4) Full colour: 26 images per minute
Resolution:	Maximum 600 dpi
Original size:	A5 - A3
Bundled drivers:	TWAIN Network

### SOFTWARE

 SmartDeviceMonitor™
Web SmartDeviceMonitor™
Web Image Monitor
DeskTopBinder™ Lite/Professional/v.5

### FAX (option)

 Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3
Modem speed:	Maximum 33.6 Kbps
Resolution:	200 x 100/200 dpi
Compression method:	MH, MR, MMR, JBIG
Scanning speed:	36 sheets per minute
Memory capacity:	Standard: 4 MB
Memory backup:	Yes

### OTHER OPTIONS

500-sheet paper tray, 2 x 500-sheet paper trays, Caster table, Cabinet, Inner one bin tray, Side tray, PCL module, Fax unit, Fax stamp ink, Copy Data Security Unit, PictBridge, Counter interface unit type A, Key counter bracket, Remote communication gate BN1.

<sup>1</sup> Warm-up time and power consumption may differ depending on the conditions and environment of the machine.

For availability of models, optional apparatus and software, please contact your local Ricoh supplier.